



Creativity Progress & Excellence

Network Product





LD2322X

Day & Night 1080P HD Vari-Focal Dome IP Camera



Features

- Full HD 2 megapixel CMOS image sensor
- True H.264 AVC/MPEG-4 part 10
- H.264 and Motion JPEG multi-profile video streaming
- 3D noise reduction (MCTF)
- 2D WDR function
- Digital zoom supported
- Audio / Motion detection alarm function
- Ceiling mount and Embedded mount installation
- Day & Night (IR cut removable)
- 2-way audio supported
- Digital I/O : 1 in, 1 out
- ONVIF supported

Dimensions $\Phi 150 \times 134\text{mm}$



IP CAMERA SERIES			
Day & Night 1080P HD Vari-Focal Dome IP Camera			
Model	LD2322EX3.6		
Lens	Focal Length	3.3 ~ 12 mm	
	Iris	F1.4	
	Angle of View	H	59.6° ~ 22.6°
		V	33.5° ~ 12.9°
D		68.4° ~ 25.9°	
Pick Up Element	1/2.5" CMOS image sensor		
Effective Pixels	1920 (H) x 1080 (V) = 2,073,600 (pixel)		
Chip Size	5.70mm (H) x 4.28mm (V)		
Scanning System	Progressive Scan		
Infrared Cut Filter	Auto / Schedule / Day (Color) / Night (Mono)		
Min. Illumination	0.25 Lux at F1.4 (Low Light Mode)		
White Balance	Auto / Tungsten / Indoor / Fluorescents1 / Fluorescents2 / Outdoor1 / Outdoor2		
Back Light Compensation	Off / On		
Electronic Shutter	1/30(25)s ~ 1/8000s		
Sense Up	Off / 1 Frame / 2 Frames / 3 Frames / 7 Frames		
Sense Up Plus	Yes		
Auto Gain Control	36 dB Variable Gain		
3D Noise Reduction	Off / 1 ~ 32 Selectable		
2D WDR	Off / x2 / x3 / x4		
Privacy Masking	Off / On (4 zones)		
Image Effects	Brightness, Contrast, Hue, Saturation, Sharpness, Mirror, Flip		
Live Video Output	CVBS 1.0Vp-p, 75 ohm, RCA connector		
Audio In / Output	Mono, 1.4 Vp-p, 50 K Ω , 3.5mm phone jack		
Operating Temperature	-25°C ~ +50°C (-13°F ~ 122°F)		
Dimension	$\Phi 150 \times 134\text{mm}$		
Weight	600g		
Power Supply	DC12V $\pm 10\%$ / PoE (IEEE 802.3af compliant)		
Power Consumption	DC12V, 6W / PoE, 7.5W		

NETWORK	
Video Compression	H.264, Motion JPEG
Resolution	1080P(1920 x 1080), 720P(1280 x 720), D1(720 x 480), CIF(352 x 240)
Maximum Frame Rate	H.264 : up to 15 fps @ 1920 x 1080, 30fps @ 1280 x 720, 30fps @ 720 x 480 Motion JPEG : up to 15 fps @ 1920 x 1080, 30 fps @ 720 x 480, 30 fps @ 352 x 240
Video Streaming Protocol	RTP/HTTP, RTP/TCP, RTP/UDP/Multicast
Video Bitrate	128Kbps ~ 5Mbps Frame rate and bit rate controllable on-the-fly VBR / CBR / GOP supported
Security	Base64 HTTP encryption Multiple user access levels with password protection 10 user accounts available
Users	8 simultaneous users
Digital Zoom	Yes
OSD	Text overlay for date, time, and camera name
Alarm Function	Alarm / motion detection triggering recording into SD card Image upload over FTP and E-mail by audio / motion detection
CPU, Memory	Embedded SoC ARM11, 528MHz, 256MB DDR2, 256MB flash memory
Maintenance	Firmware update via HTTP Firmware available at web site
Network Interface	10Mbps / 100Mbps Base-T, RJ-45
PC Requirement	OS : Windows 2000, Windows XP, Windows Vista, Windows 7 Browser : Windows Internet Explorer 6, 7, 8 CPU : Intel Pentium 4 1.8GHz or above RAM : 1GB or above, Independent Display Card
Network Protocols	IP, TCP, UDP, HTTP, SMTP, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ONVIF, ICMP, IGMP
Mobile Phone and PDA	iPhone, iPad, and Android support
System Integration	ONVIF & LILIN HTTP API CMX HD 3.6 support
Video Display	LILIN Universal ActiveX & LILIN Java Applet
OS	Embedded Linux 2.6.32
Two-way Audio	G.711 / PCM
SD Card Recording	Support Micro SD/SDHC card for circular recording (card is not included)
Alarm Input / Output	Digital 1 input (TTL, +3 ~ 5V) / 1 Output (N.O.)